


****为防止LCD产生图像残留，在使用常黑面板时不要长时间显示固定图案。如果LCD需要显示固定图案，建议时间少于2分钟或者更短的时间内刷新显示内容一次或多次。
 ***In order to prevent the LCD from producing image retention, do not display a fixed pattern for a long time when using a normally black panel. If the LCD needs to display a fixed pattern, it is recommended to refresh the display one or more times in less than 2 minutes or less.
 强烈建议使用黑色图像或移动图像作为屏幕保护程序。It is strongly recommended to use a black image or moving image as a screen saver.

A B C D

图纸字体：黑体
 Drawing Font: Bold

A TFT Pin_SIGNAL

1	LEDA	21	NC
2	LEDK	22	NC
3	GND	23	NC
4	D3P	24	VCI
5	D3N	25	VCI
6	GND	26	NC
7	D2P	27	GND
8	D2N	28	NC
9	GND	29	NC
10	DCKP	30	NC



HOT HDMI

TFT 观看角度 TFT Viewing Di retion	U80/D80/R80/L80 (Typ.)	TFT 工作温度 TFT Operatin Temp	-30 °C ~ +80 °C
TFT 接口 TFT Interface	MIPI or LVDS	TFT 储存温度 TFT Storage Temp	-30 °C ~ +80 °C
工作电压 Operating Voltage	V _{CI} = 3.3 ± 0.3V	背光驱动条件 Backlight conditions	V _f = 18.0 ± 1.5V, If = 100 mA
驱动芯片 Driver IC	T. B. D <TFT>	液晶模组亮度 LCD Brightness	1600 ± 100 cd/m ² / 恒流测试 LCD Brightness